

# Tableau de comparaison des poids des aciers galvanisés à chaude au trempé

kg/m<sup>2</sup>

Revêtement Épaisseur(mm)	Z06 045	Z08 060 030 / 090	Z10 030/120 060/090	Z12 090 030/150 060/120	060/150	Z18 120 090/150 060/180	Z20	Z22	Z25	Z27
0.25	2.053	2.083	2.113	2.146	2.173	2.207	2.248	2.268	2.268	2.344
0.27	2.210	2.240	2.270	2.303	2.330	2.364	2.405	2.425	2.425	2.501
0.30	2.445	2.475	2.505	2.538	2.565	2.599	2.640	2.660	2.660	2.736
0.35	2.838	2.868	2.898	2.931	2.958	2.992	3.033	3.053	3.053	3.129
0.40	3.230	3.260	3.290	3.323	3.350	3.384	3.425	3.445	3.445	3.521
0.50	4.015	4.045	4.075	4.108	4.135	4.169	4.210	4.230	4.230	4.306
0.60	4.800	4.830	4.860	4.893	4.920	4.954	4.995	5.015	5.015	5.091
0.70	5.585	5.615	5.645	5.678	5.705	5.739	5.780	5.800	5.800	5.876
0.80	6.370	6.400	6.430	6.463	6.490	6.524	6.565	6.585	6.585	6.661
0.90	7.155	7.185	7.215	7.284	7.275	7.309	7.350	7.370	7.370	7.446
1.0	7.940	7.970	8.000	8.033	8.060	8.094	8.135	8.155	8.155	8.231
1.2	9.510	9.540	9.570	9.603	9.630	9.664	9.705	9.725	9.725	9.801
1.4	11.08	11.11	11.14	11.17	11.20	11.23	11.28	11.30	11.30	11.37
1.6	12.65	12.68	12.71	12.74	12.77	12.80	12.85	12.87	12.87	12.94
1.8	14.22	14.25	14.28	14.31	14.34	14.37	14.42	14.44	14.44	14.51
2.0	15.79	15.82	15.85	15.88	15.91	15.94	15.99	16.01	16.01	16.08
2.3	18.15	18.18	18.12	18.24	18.27	18.30	18.34	18.36	18.36	18.44
2.8	22.07	22.10	22.13	22.16	22.19	22.22	22.27	22.29	22.29	22.36
3.2	25.21	25.24	25.27	25.30	25.33	25.36	25.41	25.43	25.43	25.50
3.6	28.35	28.38	28.41	28.44	28.47	28.50	28.55	28.57	28.57	28.64
4.0	31.49	31.52	31.55	31.58	31.61	31.64	31.69	31.71	31.71	31.78
4.5	35.42	35.45	35.48	35.51	35.54	35.57	35.61	35.63	35.63	35.71
6.0	47.19	47.22	47.25	47.28	47.31	47.34	47.39	47.41	47.41	47.48

Notes:

- 1.Poids des matériaux de base:épaisseur(mm)xlargeur(m) x longueur(m) x densité(7.85)
- 2.Poids des aciers galvanisés :poids des matériaux de bas + poids de revêtement du zinc.

## Tableau des revêtements en zinc

Revêtement	Z06 045	Z08 060 030 / 090	Z10 030/120 060/090	Z12 090 030/150 060/120	060/150	Z18 120 090/150 060/180	Z20	Z22	Z25	Z27
Poids (kg/m <sup>2</sup> )	0.090	0.120	0.150	0.183	0.210	0.244	0.285	0.305	0.305	0.381



ISO9001 國際品質認證  
**毅承股份有限公司**  
 專營熱浸鍍鋅、鍍合金鋼材、不銹鋼等材料供應  
 YE CHIME CO.,LTD

**TRADO**.COM